



### Product Identification

880777

- OLI120 Mechanic OLIpure

### Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications
- Flush cistern with interior cleaning system for WC pan
- Compatible with all floor mounted WC pans

### Technical Features

- Dual flush in-wall cistern 6/3 litres (adjustable to 4/2 and 7/3 compatible with dual flush actuators (Narrow OLIpure and Glam OLIpure)
- 126mm thickness
- Mechanic actuation
- Equipped with Azor Inlet Valve
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- EN 14055 marking CL1
- Other versions compliant with: NF/KIWA/BELGAQUA standards
- Supplied with anti-condensation lining
- Net for easier mortar adhesion

Millimetres measures

## OLIpure System

- Simple refilling system through a control plate of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) \*
- Storage capacity:450ml

## Accessories

- 1 Flush pipe  $\varnothing 55 \times 360$
- 1 Seal for flush pipe  $\varnothing 45$
- 1 Protective box
- 1 G  $\frac{1}{2}$ " stop valve
- 1 Protection sponge for the stop valve
- 2 Metal plates for fixation
- 1 WC connection pipe  $\varnothing 45 \times 180$

## Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

## Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)

Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)  
cp\* is a unit of measure of viscosity, it reads "centipoise"