



Product Identification

885068

- OLI74 Nano Plus Mechanic

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications

Technical Features

- Dual flush of 6/3 liters (adjustable to 4/2 liters)
- Mechanic actuation
- Working pressure from 0,5 to 10 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- CE EN 14055 marking CL1
- Equipped with Nano Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

Accessories

- 1 Flush pipe \varnothing 56 x 260
- 1 Seal for flush pipe \varnothing 45
- 1 Protective box
- 1 G 1/2" stop valve
- 1 Protection sponge for the stop valve
- 2 Metal plates for fixation
- 1 Discharge pipe protection cover in EPS

Fixing accessories for metal plates

- 2 Screws ZN M5x16
- 2 Washers ZN M5
- 2 Nuts M5

Warranty

For the terms of warranty please visit www.oli-world.com

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com