



(dimensions in millimeters)

Product Identification

721005

- Expert Plus Pneumatic

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications.
- Top or front activation/access
- Compatible with all floor mounted WC pans

Technical Features

- Dual flush in-wall cistern compatible with dual flush actuators 6/3 litres (adjustable to 4/2 and 7/3)
- Pneumatic actuation
- 150mm thickness
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene cistern highly resistable and inalterable to thermal stress
- Lower/under bench installation possibility
- Other versions compliant with: WRAS/SAI-WATWERMARK/SINTEF/NF/BELGAQUA standards
- EN 14055 marking CL1
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

Accessories

- 1 Discharge pipe 315mm
- 1 Seal for discharge pipe ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Protection pipe ø 45
- 1 WC connection pipe ø45 x 180

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com