



Product Identification

600051

- OLI80 Mechanic

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications

Technical Features

- Dual flush of 6/3 in-wall cistern compatible with either dual or single flush actuators
- Adjustable flush volumes
- 80mm thickness
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: BELGAQUA standards
- EN 14055 marking CL1
- Silent Valve category Class 1
- Supplied with anti-condensation lining

Millimetres measures

Accessories

- 1 Discharge pipe \varnothing 56 x 260
- 1 Seal for discharge pipe \varnothing 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 2 Metal plates for fixation
- 1 WC connection pipe \varnothing 45

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com