



## Product Identification

722021

- Quadra Plus Mechanic Free Standing

## Definition and Application

- Preassembled structure to be secured to the floor only for the installation of wall-hung pans inside light walls
- Compatible with all wall-hung WC pans with a 180mm fixation length

## Technical Features

### Structure

- Metal, corrosion resistant
- Height adjustable from 0 to 150mm
- 300mm, reduced width
- Depth adjustable outlet bend
- Tested for 400kg load

### **Cistern**

- Dual flush of 6/3 in-wall cistern compatible with either dual or single flush actuators 6/3 litres (adjustable to 7/3)
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- 187mm thickness
- 270mm reduced width
- Mechanic actuation
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: NF standards
- EN 14055 marking CL1
- Supplied with anti-condensation lining

### **Accessories**

- 1 Discharge pipe  $\varnothing$  90 x 315
- 1 Seal for discharge pipe  $\varnothing$  125
- 1 Connecting pipe  $\varnothing$  45 x 180
- 1 Pan rubber seal  $\varnothing$  45
- 1 Protective box
- 1 G  $\frac{1}{2}$ " stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend  $\varnothing$  90 / 90 L230
- 1 Protection pipe  $\varnothing$ 90
- 1 Adaptor pipe  $\varnothing$  90/110

### **Fixing accessories for floor structure**

- 4 Bushing M10

### **Fixing accessories for toilet bowl mounting on the structure:**

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Washers for WC pan fixation
- 2 Nuts M12
- 2 Washers  $\varnothing$  34

## **Warranty**

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

## **Observations**

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)