



### Product Identification

048159

- Adjustable frame Easy Move

### Definition and Application

- Easy Move WC frame is compatible with all wall-hung WC pans (with max 660mm length)
- Ergonomic system adjustable in height by 150mm
- Installation in resistant walls and frontal finishing in masonry and plasterboard walls
- Available for lift-up support rail installation

### Technical Features

#### Structure

- Painted tubular with 2mm thickness, corrosion resistant
- Height adjustable from 0 to 150mm
- Easy installation with Fasf Fit System
- Tested for 400kg load
- Mechanical adjustment system operated by one low-voltage motor, that allows height adjustment through a remote control

Millimetres measures

### Cistern

- Dual flush of 6/3 litres
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with KIWA/UPC/SAI/WRAS/Watermark standards
- EN 14055 marking CL1
- Equipped with Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

### Accessories

- 1 Discharge pipe  $\varnothing$  90 x 250
- 1 Seal discharge pipe  $\varnothing$  125
- 1 Connection pipe  $\varnothing$  45 x 180
- 1 Pan rubber seal  $\varnothing$  45
- 1 Protective box
- 1 G  $\frac{1}{2}$ " stop valve
- 1 Protection sponge for the stop valve
- 1 Outlet bend  $\varnothing$  90
- 1 Adaptor  $\varnothing$  90//110
- 1 Protection pipe  $\varnothing$  90
- 1 Protection pipe  $\varnothing$  45
- 1 Wood panel
- 1 Remote control

### Fixing the structure to the wall and floor

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure
- 2 Fast Fit fixing

### Fixing accessories for toilet bowl mounting on the structure:

- 2 Threaded rods M12
- 2 Nuts M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Washers Zn  $\varnothing$  34

## Motor

- Silent electric engine;
- Mains supply: 220V/110 (50/60Hz);
- Power: 350 Watt;
- Insulation rating: IP66;
- Movement velocity of: 28mm/s;
- Push power: 6000N (ca 600kgf);
- Traction power 3000N (ca 300kgf);
- Limit switch;

## Warranty

### Frame

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product
- If the product is not correctly installed the warranty is not valid

### Eletronical components

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product
- If the product is not correctly installed the warranty is not valid

## Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)