



Product Identification

714001

- WC Sanitarblock

Definition and Application

- Preassembled structure for built-in or plasterboard wall installation
- Compatible with all wall-hung WC pans

Technical Features

Structure

- Painted tubular frame with 1,5mm thickness, corrosion resistant
- Height adjustable (0 – 200 mm)
- Frame tested for 400kg load
- Depth adjustable outlet bend
- WC with two fixation points

Accessories

- 1 Flush bend \varnothing 90 / 90 L230
- 1 Pipe protection \varnothing 90
- 1 Evacuation pipe \varnothing 90 x 250
- 1 Connecting pipe \varnothing 45 x 180
- 1 Pan rubber seal \varnothing 45
- 1 Seal for discharge pipe
- 1 Adaptor \varnothing 90/110

Fixing accessories for wall and floor structure

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure

For fixing WC to structure

- 2 Threaded rods M12
- 2 Nuts M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Washers Zn \varnothing 34

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com