



## Product Identification

151339

- OLI120 PLUS Mechanic Block

## Definition and Application

- Pre-assembled structure for setting in masonry walls, to installation of wall-hung sanitary appliances
- Compatible with all wall-hung WC pans

## Technical Features

Millimetres measures

## Structure

- Metal, galvanized, corrosion resistant

## Cistern

- Dual flush in-wall cistern compatible with either dual or single flush actuators 6/3 litres (adjustable to 4/2 and 7/3)
- 144mm thickness
- Mechanic actuation
- Equipped with Azor Plus Inlet Valve, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- EN 14055 marking CL1
- Other versions compliant with: WRAS/NF/KIWA/BELGAQUA standards
- Supplied with robust Anti-condensation lining

## Accessories

- 1 Flush pipe  $\varnothing 90 \times 250$
- 1 Seal for flush pipe  $\varnothing 125$
- 1 Connecting pipe  $\varnothing 45 \times 180$
- 1 Pan rubber seal  $\varnothing 45$
- 1 Protective box
- 1 G  $\frac{1}{2}$ " stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend  $\varnothing 90 / 90$  L230
- 1 Outlet bend and  $\varnothing 90/110$  adaptor
- 1 Protection pipe  $\varnothing 90$

### Fixing accessories for wall structure:

- 3 Galvanized screws M8x70
- 3 Galvanized washers M8 DIN 9021
- 3 Bushing M8

### Fixing accessories for toilet bowl mounting on the structure:

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Nuts M12
- 2 Washers  $\varnothing 34$

## Warranty

- For the terms of warranty please visit [www.oli-world.com](http://www.oli-world.com)

## Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)