

Product Identification

101775

- OLI74 PLUS Mechanic HAPPY AIR

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications
- Compatible with all floor mounted WC pans
- Extraction of odours and air renewal system in bathroom

Technical Features

- Dual flush in-wall cistern compatible with either dual or single flush actuators 6/3 litres
- Mechanic actuation
- 80mm thickness
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with WRAS/NF/SAI-WATERMARK/UPC/KIWA standards
- EN 14055
- Equipped with Azor Plus Inlet Valves, with delayed refilling (saves up to 9 litres of water per day) and silent according to the NF standard category Class I
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

Millimetres measures

Accessories

- 1 Discharge pipe \varnothing 56 x 360
- 1 Seal for discharge pipe \varnothing 40/45
- 1 Protective box
- 1 G 1/2" stop valve
- 1 Protection sponge for the stop valve
- 2 Metal plates for fixation
- 1 Discharge pipe protection cover in EPS
-

Fixing accessories for metal plates

- 2 Screws ZN M5x16
- 2 Washers ZN M5
- 2 Nuts M5


Order separately

Happy Air PLUS code 880377

- It can be installed on the wall or ceiling
- Activated by switch or sensor
- 960 Lumen LED
- Humidity sensor that can be set to automatically turn on
- Possible to adjust the operating time after the user switches the switch off (2min20min)
- Anti-back flow valve
- Paintable cover panel
- Melamine filter – noise reduction

Technical Data

- Frequency: 50hz
- Power Supply: 220V
- The extractor fan operates at 220V/50Hz
- Active current: 0.14 A
- Power: 31W
- Insulation: IP35



Performance Data

- Capacity 85m³/h- 12W 34dB
- Capacity 100m³/h- 20W 38dB.
- Maximum suction pressure: 190 Pa
- Rotating speed: 1900rpm

Warranty

Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.

If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com