



Product Identification

880782

- OLI74 Mechanic OLIpure

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications
- Flush cistern with interior cleaning system for WC pan
- Compatible with all floor mounted WC pans

Technical Features

- Dual flush in-wall cistern 6/3L compatible with dual flush actuators (Narrow OLIpure and Glam OLIpure)
- Mechanic actuation
- 80mm thickness
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with SAI-WATERMARK/UPC/KIWA standards
- EN 14055
- Equipped with Azor Inlet Valve
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

Millimetres measures

OLIpure System

- Simple refilling system through a control plate of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) *
- Storage capacity:450ml

Accessories

- 1 Discharge pipe \varnothing 56 x 360
- 1 Seal for discharge pipe \varnothing 40/45
- 1 Protective box
- 1 G 1/2" stop valve
- 1 Protection sponge for the stop valve
- 2 Metal plates for fixation
- 1 Discharge pipe protection cover in EPS

Fixing accessories for metal plates

- 2 Screws ZN M5x16
- 2 Washers ZN M5
- 2 Nuts M5

Warranty

Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.

If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com

Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)
cp* is a unit of measure of viscosity, it reads "centipoise"