



## Product Identification

880787

- Expert Mechanic OLIpure Sanitarblock 820

## Definition and Application

- Preassembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall
- Compatible with all wall-hung WC pans
- Top or front activation/access
- Flush cistern with interior cleaning system for WC pan

## Technical Features

### Structure

- Metal with 820mm, with 1,5mm thickness and corrosion resistant
- Easy and quick installation
- Minimum thickness of 150mm and adjustable up to 200mm
- Height regulation of the adjustable floor brackets (0-200 mm);
- Depth adjustable outlet bend
- Tested for 400kg load

### Cistern

- Dual flush in-wall cistern 6/3 litres (adjustable to 4/2 and 7/3) compatible with dual flush actuators (Narrow OLIpure and Glam OLIpure)
- 150mm thickness
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene cistern highly resistable and inalterable to thermal stress
- Lower/under bench installation possibility
- Other versions compliant with: SAI-WATERMARK/NF/BELGAQUA standards
- EN 14055 CE marking
- Equipped with Azor Inlet Valve
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

### OLIpure System

- Simple refilling system through a control plate of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) \*
- Storage capacity:450ml

### Accessories

- 1 Discharge pipe ø 90 x 250
- 1 Seal for discharge pipe ø 125
- 1 Connecting pipe ø 45 x 180
- 1 Pan rubber seal ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend ø 90 / 90 L230
- 1 Protection pipe Ø90
- 1 Protection pipe Ø45
- 1 Adaptor pipe ø 90/110

#### Fixing accessories for wall structure:

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure

#### Fixing accessories for toilet bowl mounting on the structure

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Washers for WC pan fixation
- 2 Nuts M12
- 2 Washers ø 34

## Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

## Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site [www.oli-world.com](http://www.oli-world.com)

\*Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)  
cp\* is a unit of measure of viscosity, it reads "centipoise"