



(dimensions in millimeters)

Product Identification

152966

- Expert Mechanic OLIpure

Definition and Application

- Flush cistern to be installed inside the wall and used in combination with floor standing sanitary applications.
- Top or front activation/access
- Flush cistern with interior cleaning system for WC pan

Technical Features

Millimetres measures

- Dual flush in-wall cistern 6/3L (adjustable to 4/2 and 7/3) compatible with dual flush actuators (Narrow OLIpure and Glam OLIpure)
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene cistern highly resistable and inalterable to thermal stress
- Lower/under bench installation possibility
- Other versions compliant with: SAI-WATWERMARK/SINTEF/NF/BELGAQUA standards
- EN 14055 CE marking
- Equipped with Azor Inlet Valve
- Supplied with anti-condensation lining
- "A" class for the Water Efficiency in compliance with the ANQIP Authority requirements

OLIpure System

- Simple refilling system through a control plate of the cistern
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) *
- Storage capacity:450ml

Accessories

- 1 Discharge pipe 315mm
- 1 Seal for discharge pipe ø 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Protection pipe ø 45
- 1 WC connection pipe ø45 x 180

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com

Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)
cp* is a unit of measure of viscosity, it reads "centipoise"