



Product Identification

154961

- Quarzo OLIPure

Definition and Application

- OLI exposed cistern to medium/low level installation

Technical Features

- Dual flush 6/3 litres (adjustable to 9/4 litres in the outlet valve)
- White PS material
- 145mm thickness
- Silent inlet valve
- Acoustic and anti-condensation internal lining
- Adjustable wall fixation system
- Water supply connection – Lateral and back (a bended connection pipe or flexible hose it's needed)
- "A" class for the water efficiency in compliance with the ANQIP authority requirements.
- Other versions compliant with; EN 14055

OLIpure System

- Simple refilling system through a discreet nozzle on the side
- Compatible with all the existents detergent on the market (except those containing hydrochloric acid) *
- Storage capacity:450ml

Millimetres measures



Accessories

- 1 Flush pipe Ø50/40
- 1 Seal for flush pipe Ø40
- 1 Rubber seal
- 1 Washer
- 2 Suspension fasteners
- 2 Bushing 6mm
- 2 Screws Ø4,2X25
- 1 Nut 3/8

Warranty

Five (5) years warranty according to the general selling terms, starting from the purchase date of the product.

If the product is not correctly installed the warranty is not valid

Observations

There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com

Is recommended the use of chlorine-free liquid detergents with a viscosity between 150 and 300 cp (at 20 ° C)
cp* is a unit of measure of viscosity, it reads "centipoise"