



Product Identification

879808

- STOP FIRE

Definition and Application

Millimetres measures

- It prevents the spread of fire and smoke between divisions in a building for approximately 120 minutes. Application for control plates and in wall cisterns OLI

Technical Features

- The “collars” are made of steel and painted with polyester powder fitted with special intumescent inserts which, in the event of fire, expand and squeeze the pipe thus preventing the passage of flames, combustion gas and vapours and acting as a thermal insulation. With 27% mineral graphite and are rated B2 according to DIN 4102;
- Product compliant with EN 13501-2:2'16

Accessories

- 4 fixation screws PH2 D4.8X16
- 2 fixation screws DIN933 M4X25 ZN 8.8
- 1 Set for opening control plate
- 2 Supports for application on Expert Plus in wall cistern
- 1 Set for flushes pipes

Compatible with OLI in wall cisterns:

- OLI74 PLUS minimum frontal wall thickness 30mm;
- OLI120 PLUS minimum frontal wall thickness 40mm;
- QUADRA PLUS minimum frontal wall thickness 30mm;
- OLI120 minimum frontal wall thickness 40mm;
- EXPERT PLUS minimum frontal wall thickness 30mm.

Compatible with OLI control plates:

- GLAM;
- NARROW;
- GLOBE;
- PLAIN.

Warranty

- Two (2) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

- For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com